Standard Pharmacy Refrigerator with data logger

Model: QSPR420

Features:

Forced-air cooling with optimized air distribution system designed. To achieve maximum temperature uniformity and stability. Optimized refrigeration system design for more effective cooling and speedy recovery. USB and Data logger.

Specifications:

- Capacity: 100 to 416 L
- Dimension: (W*D*H): Internal (mm): 685*429*1380
- External (mm): 785*552*1927/variable
- Temperature: Range (°C) at RT. 10 ~ 32 (°C): 2 ~ 8
- Sensor: NTC
- Controller: Microprocessor
- Cooling System: Refrigerant: R290 (CFC Free
- Defrost: Auto
- Compressor qty: 1
- Display: Digital Display.
- Audible &Visible Alarm:
- High / Low temperature: Standard
- Power failure backup system(alarm): 8h
- Door ajar: Standard
- Material:
- Internal: Electro-galvanized steel with
- antimicrobial powder coating
- External: Electro-galvanized steel with
- antimicrobial powder coating

Accessories:

- USB port: Included
- Printer: Included
- Printer Roll: 5 pcs
- Casters: Standard
- Data logger: Included
- Remote alarm port: Standard
- Test hole (Qty) / Diameter (mm): 1 / 25
- Shelves / Drawers (Qty): Shelves / 5
- Sound Emission (dB): 50

Electricity:

Voltage/Frequency: AC110 /220V±10%, 50/ 60Hz Consumption (W): 280 N.W. / G.W. (kg): 120 / 133/variable



Air Drying Oven

Model: QS30-V240 AB Series

Features:

- Temperature range: RT+10-250°C(A series); RT+10-300 °C(B series)
- Test hole Optional φ 25,50,80mm
- Safety device: Leakage protector/Over- temperature alarm
- Capacity(L): 30 to 600 L
- Sensor PT100
- Timer(min) : 1-9999

